

# ACA15 ADHESIVE

## ACOUSTIC MAT ADHESIVE

### TECHNICAL DATA SHEET

ACA15 offers excellent plasticizer resistance and is specially designed for installing a wide range of vinyl and acoustic floor coverings.

- **Pre Mixed Adhesive**
- **Easy spread formulation**
- **Remains permanently flexible**
- **Quick and easy to install**
- **Offers long term performance**
- **Pressure sensitive**



Ideal product for commercial applications e.g. shopping centres, high rise buildings and residential.

Low VOC content- meets Green Building Council of Australia Green Star IEQ-13 requirements.



# ACA15 ADHESIVE

## ACOUSTIC MAT ADHESIVE

---

### Characteristics

ACA15 is specially formulated for the installation of commercial and residential acoustic mat underlay, it has high initial grab and is ideal for bonding both vinyl and acoustic mats.

### Preparation

Ensure new concrete is allowed to cure for a minimum of 5 days. Ensure all surfaces are sound, dry and free from oil, dust, grease, wax, curing compounds, release agents and any other contaminating materials. It is recommended that all dry and porous surfaces should be primed first using Nova Prime and Non porous surfaces primed using Optimus Primer.

### Application

Once the substrate has been correctly prepared in accordance with the above instructions, apply ACA15 adhesive on substrate using a 4mm "V" notched trowel or roller. Allow adhesive to tack up before installing Acoustic Mat. Roll Acoustic Mat onto tacky adhesive and using a plastic float bed ensuring total coverage in contact with the mat and substrate.

### Packaging

ACA15 Adhesive comes in a 15ltr Pail covering 11m<sup>2</sup> per litre.

### Cleaning

Keep out of sewers and storm water. Sweep up spills. ACA15 Adhesive can be cleaned off equipment with warm water, providing the compound has not dried.

### Shelf Life

ACA15 Adhesive has 12 months when stored in a dry place, in original unopened packaging.

### Precautions

Keep area well ventilated.

Do no use in wet areas without the application of a waterproofing membrane.

### Disclaimer

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Novatex Products shall not be liable for any inaccuracy in the information given or for any loss, injury or damage whatsoever resulting from its use. To the full extent permitted by law, Novatex Products liability is limited to its discretion, to replacement of goods or the supply of equivalent goods. For applications/situations not mentioned on this packaging, please contact your nearest Novatex office.



# ACA15 ADHESIVE

## ACOUSTIC MAT ADHESIVE

### Technical data

Appearance	pre mixed adhesive
Material	Recycled rubber granulate bonded with cold-cure PUR
Granulate structure	fine
Mass density kg/m <sup>3</sup> DIN EN ISO 845	730 kg/m <sup>3</sup> +/- 5%
Dimensions	1m x 1.05m x 3mm
Footfall sound insulation DIN EN ISO 140-8	21 dB at 3 und 5mm under 7 mm standard laminate flooring
Chair roll suitability DIN EN ISO 425	Yes
Tensile Strength DIN EN ISO 1798	0.09N/mm <sup>2</sup>
Under floor heating	Yes
Elongation at break DIN EN ISO 1798	min. 30%
Temperature stability	-40 to + 110 °C
Fire Classification	B2

### Contact Us

For further technical information, please contact Novatex Products on 02 9757 3525.



Novatex Products Pty Ltd  
ABN:55 003 032 328  
P O Box 7123  
Wetherill Park NSW 2164



Telephone: 029757 3525  
Facsimile: 02 9757 3454  
Email: [info@novatexproducts.com.au](mailto:info@novatexproducts.com.au)  
Website: [www.novatexproducts.com.au](http://www.novatexproducts.com.au)