

# Material Safety Data Sheet

Page: 1 of 3

Reference No. MSDS01 Issue Date: 4<sup>th</sup> December 2015 ISSUED by Novatex  
Product Name: **Ezy Render, ER 100, EZ 101, Fine Skim, Medium Float, Coarse Float,  
Scratch and Drag, Insulclad Base, Hi Build Lo Weight**

Not Classified as Hazardous according to criteria of Worksafe Australia

## COMPANY DETAILS

**Company Name** Novatex Products Pty Ltd  
**Address** 118 Hassall Street, WETHERILL PARK NSW 2164  
**Tel/Fax** Ph: (02) 9757 3525 Fax: (02) 9757 3424

## IDENTIFICATION

**Product Name** Ezy render, ER 100, EZ 101, Fine Skim, medium Float, coarse Float, Scratch and Drag, Insulclad base, High Build Lo weight  
**Other Names** None Allocated  
**UN Number** None Allocated  
**Poisons Schedule** Not Scheduled  
**Product Use** Finish render for walls.

## Physical Data

**Appearance** Off-white powder.  
**Boiling Point** Not applicable.  
**Melting Point** <1200°C.  
**Bulk Density** 1200-1500 kg/m<sup>3</sup>  
**Flash Point** Not applicable.  
**Flamm. Limit LEL** Not applicable.  
**Solubility in Water** <10 gms/litre.

## Other Properties

**Evaporation Rate** Not applicable.  
**Vapour Density** Not applicable.  
**Physical State** Solid (powder)  
**Stability** Stable.  
**pH** Solution pH: 11  
**Materials to Avoid** Strong acids.

## Ingredients

Ingredients	Name	CAS	Proportion
	Quartz sand	14808-60-7	>60%
	Portland cement	65997-15-1	10-30%
	Hydrated Lime	1305-62-0	10-30%

**Other Information** Proprietary ingredients determined not to be hazardous, <10%.  
Render may contain up to 3% respirable silica, depending on raw materials sources.

## HEALTH HAZARD INFORMATION

### Health Effects

**Acute - Swallowed** Alkaline corrosive to mouth and throat. May cause chemical burns and abdominal pain.  
**Acute - Eye** Corrosive eye irritant. May cause chemical conjunctivitis, reddening and watering with damage to cornea.  
**Acute - Skin** Prolonged or repeated exposure with skin may result in irritation or rash. The plastic (unhardened) render may cause defatting, alkali burns and contact dermatitis. Small amounts of soluble hexavalent chromium that may be present in Portland cement may cause irritant or allergic contact dermatitis in sensitive individuals who are repeatedly exposed to wet compound.  
**Acute - Inhaled** Irritating to nose, throat and respiratory system, causing coughing and sneezing.

# Material Safety Data Sheet

Page: 2 of 3

Reference No. MSDS01 Issue Date: 4<sup>th</sup> December 2015 ISSUED by Novatex  
Product Name: **Ezy Render, ER 100, EZ 101, Fine Skim, Medium Float, Coarse Float, Scratch and Drag, Insulclad Base, Hi Build Lo Weight**

Not Classified as Hazardous according to criteria of Worksafe Australia

## First Aid

**Swallowed** Wash mouth and lips with water. Do not induce vomiting. Give water or milk to drink to dilute stomach contents. If symptoms persist, seek medical assistance.

**Eye** Immediately irrigate with copious quantity of water or saline eyewash for at least 15 minutes with the eyelids held open. In all cases of eye contamination, it is a sensible precaution to seek medical advice if irritation and discomfort persist. Continue to irrigate the eye with clean water or saline solution while transporting to medical facility.

**Skin** Wash with plenty of soap and water. Remove contaminated clothing and wash before re-use. Apply a skin moisturizer.

**Inhaled** Carefully remove persons to fresh air. If patient is severely affected, obtain medical assistance. If the person stops breathing, apply artificial respiration and other first aid techniques as required until medical assistance is obtained.

**First Aid Facilities** Eye wash fountains should be easily accessible.

## Advice to Doctor

**Advice to Doctor** Treat as for moderate to strong alkali.  
Treat symptomatically.  
Contact a poisons Information Centre.

## Other Health Hazard Information

**Other Information** The International Agency for Research on Cancer (IARC) evaluated crystalline silica in June 1997. "Crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group 1)". Cigarette smoking increases the risk of respiratory diseases. It is recommended that storage and work areas should be classified as smoke-free.

## PRECAUTIONS FOR USE

Exposure Limits	Name	TWA		STEL		Footnote
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	
	Dust NOS (Not Otherwise Specified)		10			
	Crystalline Silica (Quartz)		0.2			
<b>Other Exposure Information</b>	Where lower State or Territory exposure standards are prescribed, such lower prescribed limits should be applied. Respirable crystalline silica (Quartz) exposure levels should be kept below the recommended action level of 0.1 mg/m <sup>3</sup> . Inspirable dust levels should be kept below 2 mg/m <sup>3</sup> to minimize skin, eye and respiratory irritation.					
<b>Eng. Controls</b>	Exposure to this material may be controlled in a number of ways. Avoid generating dust. Work so as to minimize exposure to dust or repeated skin contact. Use mechanical ventilation and exhaust in work areas where dust generated by handling procedures may be released into the local environment. Dust in work areas should be controlled by regular wet sweeping or vacuuming. If dust generation can not be avoided, use personal protective equipment.					

## Personal Protection

**Protective Equip.** Avoid eye contact and repeated or prolonged skin contact. Wear overalls, safety glasses or dust resistant goggles (AS/NZ 1336), impervious gloves and waterproof boots to protect the skin from contact with the dust or particularly wet dust or compound. Use a barrier cream on exposed skin and reapply frequently. Workers should shower with soap and water after using the render. Work clothes should be laundered regularly. If inhalation risk exists, wear a class P1 or P2 particulate respirator meeting the requirements of AS/NZ 1715 and AS/NZ 1716.

# Material Safety Data Sheet

Page: 3 of 3

Reference No. MSDS01 Issue Date: 4<sup>th</sup> December 2015 ISSUED by Novatex  
Product Name: **Ezy Render, ER 100, EZ 101, Fine Skim, Medium Float, Coarse Float, Scratch and Drag, Insulclad Base, Hi Build Lo Weight**

Not Classified as Hazardous according to criteria of Worksafe Australia

## Flammability

**Fire Hazards** Product is non flammable and will not support combustion.

## SAFE HANDLING INFORMATION

### Storage and Transport

**Storage** Store and transport packaged render to prevent contact with water or the generation of dust. Store in a dry, well-ventilated area.  
**Precautions** Keep packages closed when not in use.

### Spills and Disposal

**Spills & Disposal** Do not allow to enter drains or waterways. Spills may be vacuumed or swept up. Avoid generating dust. Small amounts of waste can be disposed of in approved landfill in accordance with State and Local Government regulations.

### Fire/Explosion Hazard

**Fire/Explos.** Product is non flammable and will not support combustion. It does not cause dust explosions.

## OTHER INFORMATION

**Environ. Protection** Avoid generating dust or contaminating waterways.

## CONTACT POINT

**Preparer** Novatex Products Pty Ltd  
**Signature** 118 Hassall Street, WETHERILL PARK 2164  
Ph (02) 9757 3525  
Out of hours contact: Poisons information Centre

THE DATA SUPPLIED IN THIS MATERIAL SAFETY DATA SHEET HAS BEEN COMPILED FROM OUR SUPPLIER'S MATERIAL SAFETY DATA SHEET. THIS DATA RELATES ONLY TO THE DESIGNATED PRODUCT AND NOT TO THE USE OF SAID PRODUCTS IN COMBINATION WITH OTHER MATERIALS. BECAUSE CONDITIONS AND CIRCUMSTANCES OF USE OF THE PRODUCT ARE BEYOND OUR CONTROL AND ANY SUMMARY OF DATA SUCH AS IS REPRESENTED BY THIS MATERIAL SAFETY DATA SHEET IS INHERENTLY INCOMPLETE, TRANS CEMENT MAKE NO WARRANTY ABOUT THE ACCURACY OF THE DATA HEREIN AND ASSUME NO LIABILITY FOR THE USE OF SUCH DATA. RESPONSABILITY FOR PROPER PRECAUTIONS AND SAFE USE OF THE PRODUCT LIES WITH THE USER. ANY TECHNICAL DATA HEREIN IS ONLY FOR THE PURPOSE OF REFERENCE AND SHOULD NOT BE USED FOR CHARACTERISTICS FOR THE PRODUCT. REFER TO PRODUCT DATA SHEETS FOR ANY PRODUCT SPECIFICATION.  
...End of Report...