

NOVAMIX ADDITIVE

SPECIALLY DESIGNED ACRYLIC POLYMER ADDITIVE

TECHNICAL DATA SHEET

Nova Mix Additive an acrylic polymer additive specifically formulated to be mixed with Novatex cement based renders and adhesives to increase strength and flexibility.

Nova Mix Additive can be mixed with Novatex Grouts when grouting over substrates prone to movement e.g. timber floors, lift foyers, train stations.

Nova Mix Additive can be mixed with sand and cement for increase strength and flexibility, and mixed with neat cement as a slurry coat.



- **High polymer content giving it the capability to increase adhesion**
- **Unique formula allowing it to be mixed with any Novatex cement based product**
- **When mixed with Nova grout allows grout to be used as adhesive**

Low VOC content which easily meets Green Building Council of Australia Green Star IEQ-13 requirements.

novatex
new generation building products

Novatex Products Pty Ltd
ABN:55 003 032 328
P O Box 7123
Wetherill Park NSW 2164



Telephone: 029757 3525
Facsimile: 02 9757 3454
Email: info@novatexproducts.com.au
Website: www.novatexproducts.com.au

NOVAMIX ADDITIVE

SPECIALLY DESIGNED ACRYLIC POLYMER ADDITIVE

Mixing

When mixing with grout mix 1 part additive to 3 parts water.

When mixing with Novatex adhesives for swimming pool application mix 1 part additive to 2 parts water then use this as gauging liquid for adhesive.

When using as a slurry coat mix 1 part neat cement with 1-part Nova Mix Additive.

When mixing with Novatex Renders mix 1 part additive to 3 parts water the use this as gauging liquid for renders.

Clean up

Tools and other equipment can be cleaned up using water while the additive is still wet.

Coverage

Coverage of Nova Mix Additive will vary depending on application.

Packaging

Nova Mix Additive is available in 1 litre and 5 litre jerry cans and 20 litre cubes.

Shelf life

A pail of Nova Mix Additive, when kept in a cool, dry environment, and stored above ground level, will have a shelf life of approximately 12 months.

Precautions

Nova Mix Additive is a non-Hazardous product. It is water based and non-flammable. In case of eye contamination, rinse thoroughly with clean water. If irritation persists, seek medical advice. Do not apply where damp or Hydrostatic pressure is evident. For applications/situations not mentioned contact Novatex office.

The manufacturer is not responsible for any loss or damage arising from incorrect use. The use of this product is beyond the control of the manufacturer and liability is restricted to the replacement of material proven faulty.

Health and Safety

Nova Mix Additive is a non-hazardous product. Ensure adequate ventilation when using. If product splashes into eyes rinse thoroughly for at least 15 minutes with clean water. If Nova Mix Additive comes in contact with the skin, wash well to remove.

Manual Handling

Manual handling of this product without due care and attention, may result in personal injury.

Handy Tips

Do Not use Nova Mix Additive in temperatures above 38°C and below 5°C.

For application not mentioned in this data sheet please contact Novatex Products Pty Ltd.

For a full MSDS on this product please contact Novatex Products Pty Ltd.

Contact Us

For further technical information, please contact Novatex Products on 02 9757 3525.

Technical Data

Appearance	White Liquid
------------	--------------

