

TECHNICAL DATA SHEET

NOVAPRIME

Fine particle size acrylic primer

NovaPrime is a waterbased acrylic wall and floor primer for use on all porous surfaces before applying Novatex Tile Adhesives, Waterproofing Membranes, Renders and Leveling compound.

KEY FEATURES

- Non tacky under feet once applied
- Dries Clear

Low VOC content which easily meets Green Building Council of Australia Green Star IEQ-13 requirements.



TECHNICAL DATA SHEET

NOVAPRIME

Fine particle size acrylic primer

APPLICATION

Pour primer onto floor surface and spread using a brush, roller ensuring the entire area is fully covered with no bare patches. Allow primer to dry for approximately 5 minutes before commencing tiling, rendering, waterproofing or levelling.

CLEAN UP

Tools and other equipment can be cleaned up using water while the primer is still wet.

COVERAGE

Coverage of NovaPrime may vary depending on the porosity of the substrate. As a guide NovaPrime will cover 7m² per litre.

PACKAGING

NovaPrime is available in 5 litre jerry cans and 20 litre cubes.

SHELF LIFE

A pail of NovaPrime, when kept in a cool, dry environment, and stored above ground level, will have a shelf life of 12 months.

MANUAL HANDLING

Manual handling of this product without due care and attention may result in personal injury.

PRECAUTIONS

NovaPrime is a non-Hazardous product. It is water based and non-flammable. In case of eye contamination, rinse thoroughly with clean water. If irritation persists, seek medical advice. Do not apply where damp or Hydrostatic pressure is evident. For applications/situations not mentioned contact Novatex office. The manufacturer is not responsible for any loss or damage arising from incorrect use. The use of this product is beyond the control of the manufacturer and liability is restricted to the replacement of material proven faulty.

HEALTH AND SAFETY

NovaPrime is a non-hazardous product. Ensure adequate ventilation when using. If product splashes into eyes rinse thoroughly for at least 15 minutes with clean water. If NovaPrime comes in contact with the skin, wash well to remove.

HANDY TIPS

Do Not apply NovaPrime in temperatures below 5°C and above 35°C. For application not mentioned in this data sheet please contact Novatex Products Pty Ltd. For a full MSDS on this product please contact Novatex Products Pty Ltd. NovaPrime is classed a non-hazardous product.

TECHNICAL DATA

Appearance	Blue Liquid
Dry time	20mins @ 20°C

Disclaimer: Please note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Novatex shall not be liable for any inaccuracy in the information given or for any loss, injury or damage whatsoever resulting from its use. To the full extent permitted by law, Novatex Products liability is limited to its discretion, to replacement of goods or the supply of equivalent goods. For applications/ situations not mentioned on this packaging, please contact your nearest Novatex office. The information supplied is to the best of our knowledge true and accurate. The actual application of the product is beyond the manufacturer's control. Any failure or damage caused by the incorrect usage of the product is not the responsibility of the manufacturer. The manufacturer insists that all workmanship must be carried out in accordance with the manufacturer's specification. To the full extent permitted by law, Novatex Products Pty Ltd liability is limited to its discretion, to replacement of good or the supply of equivalent goods.

NOVATEX PRODUCTS PTY LTD

ABN:55 003 032 328

Phone: 02 9616 6500

P O Box 7123 Wetherill Park NSW 2164

Email: sales@novatexproducts.com.au

www.novatexproducts.com.au

